## AR-TO -AR PORTABLE AR CONDITONER

## Pinguino PAC T100 ECO





The new Pinguino PAC TL00 ECO portable air conditioner

Featured with on board electronic controls and remote control

Refrigerantused (R290) is completely CFC HCFC and HFC free.



TECHNICALDATA		
Dimensions (hxw xd)	mm	940x495x410
Rated voltage/frequency	V~Hz	230~50
Cooling capacity	Btu/h-₩	8000-2350
BOOST cooling capacity	Btu/h-₩	8500-2500
hputpow er	W	950
A ir flow	m³/h	250-340
Suitable for room sizes approx.		4 x 6 m
Dehum ilification capacity (only dehum ilification)	1/24h	30

## PAC 1100 ECO

- Cooling power: 8000 Btu/h (2350W)
- Inhermostat
- BOOST function: turbo boost form axim um cooling power (8500 BTU/h 2500W).
- AUTO FAN function: the appliance registers the room tem perature and autom attaly selects the best fan speed.
- 2-speed ventilation + SIENTm ode to ensure the very quietestoperation.
- Electronic tim er.
- Dehum idiferonly function, rem oves up to 30L perday
- Electronic Hum idistatto set the desired relative hum idity in dehum iditying function.
- Rem ovesm oistume (dehum idifies) whilstair conditioning mem oving up to 1L perhour
- Exclusive Condensate Recycling System
- An add tional optional hose is available to add to the air conditioner to boost efficiency bringing air from outside to cool the condenser.
- Rolling castors forease of movement

