SPLIE PO RTABLE AR CONDIED NER

Pinguino PAC S1000

THE OUETESTO PERATON



REM O TE C O NTRO L




SM ALLAND LG HT

2

ULIRAQ UICK CONNECTORS

The Electronic controls m ontorthe room idealfunction for the aircond tioner to operate attom antan

ICD mem ote controlalbws



easy and in m ediate control offunctions and noom tem perature tem perature, and select the desized noom tem perature.

The unique Pinguino S1000 is extrem ely quiet, with a noise level of 35 dB(A) it matches those levels nom ally associated with fixed high walla irconditioners.

Ulbaquick connectors forease

of installation - just snap into



Picture shows indoorunit stacked ontop of outdoor unt.

TECHNICALDATA	
Dimensions (hxw xd)	
htemalunt mm	475x450x255
Outdoorunit mm	570x542x280
Rated volage/Frequency V~Hz	230~50
Cooling capacity Btu/h-W	10000 - 2940
hputpow er W	1050
A ir flow	
htemalunt m ³ /t	a 350 <i>–</i> 250
Outdoorunt m ³ /t	n 900
Nożse kvel	
Internalunit (min-max) dB (A) 35-38
Outdoorunt dB (A) 52
Suitable for room size	4 x 7 m

PAC S1000

- Cooling power: 10000 BIU/h (2940W)
- Electronic controls with m icroprocessor
- RICD nem ote control.
- "AUTO" function: to ensure the optin um perform ance..
- Electionic timer.
- "AUTO FAN ": the appliance registers the room tem perature and autom atically ensures the optin um speed ventilation Fan only function.

phce.

- 2-speed ventilation (m ax, m ed + "bw" m ode to ensure the quietestoperation.
- 3-m eterbng connection lines with easy ulba-quick connections forease of installation.
- Outdoorunit is equipped with castors for portability.



Living innovation